




OSRAM HALOLINE R7S 78MM DIMMABLE

Housing	Glass	Colour Rendering Index (Ra)	100
Light Beam Angle	360 Degree	Control	Leading-edge dimmer, Trailing-edge dimmer
Length	74.9 mm		
Ø	12 mm		
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Colour Temperature	Luminous Flux	Power	Power Consumption	Price
332269	Colourless	2800 K	750 lm	48.0 W	48 kWh/1000h	€ 10.95
332270	Colourless	2950 K	1400 lm	80.0 W	80 kWh/1000h	€ 10.95
332271	Colourless	2950 K	2250 lm	120.0 W	120 kWh/1000h	€ 10.95



PHILIPS COREPRO LED R7S 118MM DIMMABLE

Housing	Plastic	Length	118 mm
Colour Temperature	3000 K	Ø	29 mm
Luminous Flux	1600 lm	Rated Input Voltage	220-240 V/AC
Power	14 W	Colour Rendering Index (Ra)	80
Light Beam Angle	360 Degree	Control	Leading-edge dimmer, Trailing-edge dimmer
Power Consumption	14 kWh/1000h		
Life Time L70 / B50	15000 h		

Article	Housing Color	Price
180097	Colourless	€ 45.95

