





NOBLO® SPOT 1Ph., PHASE

NOBLO® SPOT 1Ph., PHASE



220-240 V ~50/60 Hz | 150 mA
Systemleistung: 6 W
Material: Aluminium/Polycarbonate (PC)

• BEG förderfähig



220-240 V ~50/60 Hz | 350 mA
Systemleistung: 8,4 W
Material: Aluminium/Polycarbonate (PC)



740 lm | 2700 K | 750 lm | 3000 K



30 lm | 2000 K – 450 lm | 3000 K

Variante	Art.Nr.	EUR
● schwarz 2700 K	1007638	70,00
● schwarz 3000 K	1007641	70,00
○ weiß 2700 K	1007639	70,00
○ weiß 3000 K	1007642	70,00
● grau 2700 K	1007640	70,00
● grau 3000 K	1007643	70,00

Variante	Art.Nr.	EUR
● schwarz	1007352	85,00
○ weiß	1007353	85,00
● grau	1007354	85,00



Artikel	Art.Nr.	EUR
Dekoring		
● schwarz	1008482	5,90
○ weiß	1008483	5,90
● gold	1008484	5,90
● grau	1008485	5,90
● bronze	1008486	5,90
● kupfer	1008487	5,90



Artikel	Art.Nr.	EUR
Dekoring		
● schwarz	1008482	5,90
○ weiß	1008483	5,90
● gold	1008484	5,90
● grau	1008485	5,90
● bronze	1008486	5,90
● kupfer	1008487	5,90