




DASAR® 115
RL, rund, QPAR51



220-240 V ~50/60 Hz
Material: Nichtrostender Stahl 316/Glas

- Einbautopf inkl.



Socket: 1xGU10 max. Ø: 5,1 cm | L: 6 cm

Variante	Art.Nr.	EUR
● edelstahl	229320	114,00




GU10 | 2 W | 36°
230 lm | 2700 K | EEK = E
3 kW/1000h

Art.Nr.: 1007230 5,50 EUR



DASAR® 115
RL, quadratisch, QPAR51



220-240 V ~50/60 Hz
Material: Nichtrostender Stahl 316/Glas

- Einbautopf inkl.



Socket: 1xGU10 max. Ø: 5,1 cm | L: 6 cm

Variante	Art.Nr.	EUR
● edelstahl	229324	114,00




GU10 | 2 W | 36°
230 lm | 2700 K | EEK = E
3 kW/1000h

Art.Nr.: 1007230 5,50 EUR



DASAR® 115
RL, quadratisch, QPAR51



220-240 V ~50/60 Hz
Material: Nichtrostender Stahl 316/Glas

- Einbautopf inkl.



Socket: 1xGU10 max. Ø: 5,1 cm | L: 6 cm

Variante	Art.Nr.	EUR
● edelstahl	229374	114,00



GU10 | 2 W | 36°
230 lm | 2700 K | EEK = E
3 kW/1000h

Art.Nr.: 1007230 5,50 EUR

