




KALU 2.0

1PH., PHASE




220-240 V ~50/60 Hz | 250 mA
Systemleistung: 10 W
Material: Aluminium

- BEG förderfähig

KALU TRACK

1PH., QPAR111



220-240 V ~50/60 Hz
Material: Aluminium/Kunststoff



1010222	Down	2700 K
1010224		1400 lm
1010226	Down	3000 K
1010228		1450 lm
1010230	Down	4000 K
1010232		1500 lm

Variante	Art.Nr.	EUR
● schwarz 1400 lm 2700 K	1010222	149,00
● schwarz 1450 lm 3000 K	1010226	149,00
● schwarz 1500 lm 4000 K	1010230	149,00
○ weiß 1400 lm 2700 K	1010224	149,00
○ weiß 1450 lm 3000 K	1010228	149,00
○ weiß 1500 lm 4000 K	1010232	149,00



Artikel	Art.Nr.	EUR
KALU 2.0, Dekorring		
○ weiß	1010135	9,49
● schwarz	1010136	9,49
● gold	1010138	9,49
● kupfer	1010139	9,49
KALU 2.0, Linse		
○ transparent 15°	1010140	19,90
○ transparent 24°	1010141	19,90
○ transparent 36°	1010142	19,90
○ transparent 60°	1010143	19,90



Socket: 1xGU10

Variante	Art.Nr.	EUR
● schwarz	143540	77,90
○ weiß	143541	77,90
● grau	143544	77,90



GU10 | 12 W | 55°
670 lm | 2700 K | EEK = G



Art.Nr.: 1005297 86,90 EUR