

LED QT14 G9



220-240 V ~50/60 Hz
Material: Keramik
Ø: 1,8 cm | L: 5,4 cm

Lichtstrom	450 lm
Lampenstrom	0,03 A
Farbwiedergabe	90
Leistung	3,6 W

Variante	Art.Nr.	EUR
☐ transparent 400 lm 3000 K	1005286	8,80
☐ transparent 450 lm 2700 K	1007455	8,80

LED QT-DE12 R7S, 78 MM



220-240 V ~50/60 Hz
Material: Polycarbonate (PC)
Ø: 2,9 cm | L: 2,9 cm

Lichtstrom	1050 lm
Lampenstrom	0,04 A
Farbwiedergabe	90
Leistung	9 W

Variante	Art.Nr.	EUR
☐ transparent 3000 K	1005287	24,00

LED QT-DE12 R7S, 118 MM



220-240 V ~50/60 Hz
Material: Polycarbonate (PC)
Ø: 2,9 cm | L: 11,8 cm

Lichtstrom	2000 lm
Lampenstrom	0,07 A
Farbwiedergabe	90
Leistung	15 W

Variante	Art.Nr.	EUR
☐ transparent 3000 K	1005288	28,50

LED G45 E14, GOLD CURLY FILAMENT



220-240 V ~50/60 Hz
Material: Glas
Ø: 4,5 cm | L: 7,5 cm

Lichtstrom	75 lm
Lampenstrom	0,01 A
Farbwiedergabe	80
Leistung	2 W

Variante	Art.Nr.	EUR
☐ gold/transparent 70 lm 1800 K	1008649	5,09
☐ gold/transparent 75 lm 2200 K	1008650	5,09

LED C35 E14, GOLD CURLY FILAMENT



220-240 V ~50/60 Hz
Material: Glas
Ø: 3,5 cm | L: 9,8 cm

Lichtstrom	80 lm
Lampenstrom	0,01 A
Farbwiedergabe	80
Leistung	2 W

Variante	Art.Nr.	EUR
☐ gold/transparent 1800 K	1008647	5,39
☐ gold/transparent 2200 K	1008648	5,39

LED C35 E14



220-240 V ~50/60 Hz
Material: Glas
Ø: 3,5 cm | L: 9,8 cm

Lichtstrom	380 lm
Lampenstrom	0,03 A
Farbwiedergabe	90
Leistung	4,2 W

Variante	Art.Nr.	EUR
☐ transparent 2700 K	1005284	6,50