BIG WHITE®
2027

SLV LIGHTING CATALOGUE



OUTDOOR SPOTLIGHTS

OUTDOOR | SPOTLIGHTS



SYNA WIDE | 732



SYNA SHADE | 732



SYNA PLANT | 733



SYNA GARDEN | 733



SYNA | 733

NEW



PL-BEAM PRO | 734–735



GALEN | 738



GALEN PRO | 739



HELIA SPOT | 740



FLAC BEAM | 741



SAMRINA | 741



NAUTILUS 10 | 742



NAUTILUS 10 | 743



BIG NAUTILUS | 743



NAUTILUS | 744





NAUTILUS 10 SPOT | 744



DASAR® PROJECTOR | 745



DASAR® 920 | 745



HELIA SLIM | 747



THEO BRACKET | 749




LED SPIKE | 749



SITRA 360 SPIKE | 751

SYNA WIDE
SP





IP65 IK06 115° 160° 30000 h L80B10 150

220-240 V ~50/60 Hz | 500 mA
Total wattage: 5.5 W
Material: Aluminium

- IP44 safety plug


LED INSIDE CRI 80

1008478	2200 K 500 lm
1008479	3000 K 650 lm

Variant	Prod. no.	GBP
● black 500 lm | 2200 K	**1008478**	**60.00**
● black 650 lm | 3000 K	**1008479**	**60.00**

SYNA SHADE
SP, GU10





IP65 IK06 160° 150

220-240 V ~50/60 Hz
Material: Aluminium

- IP44 safety plug

SOCKET INSIDE 10 W

Base: 1xGU10 | max. Ø: 5 cm | L: 5.3 cm

Variant	Prod. no.	GBP
● black	**1008480**	**40.00**
● rust	**1012354** ●	**39.00**

GU10 | 2 W | 36°
230 lm | 2700 K | EEC = E



Prod. no.: **1007230** **5.00 GBP**

SMART


GU10 | 5 W | 100°
300 lm | 2000 K-6500 K | EEC = G



Prod. no.: **1012470** **29.00 GBP**

SYNA PLANT
SP





IP65 IK06 36° 180° 50000 h L70B30 150

220-240 V ~50/60 Hz | 300 mA
Total wattage: 6 W
Material: Aluminium

- IP44 safety plug


INSIDE CRI 80

1007146	3000 K 600 lm
1011599	2200 K 400 lm

Variant	Prod. no.	GBP
● black 600 lm | 3000 K	**1007978**	**59.00**
● black 400 lm | 2200 K	**1011599** ●	**61.00**

SYNA GARDEN
SP





IP44/ IP65 IK06 36° 300° 50000 h L70B30 150

220-240 V ~50/60 Hz | 300 mA
Total wattage: 6 W
Material: Aluminium

- IP44 safety plug


INSIDE CRI 80

1007147	3000 K 600 lm
1011598	2200 K 400 lm

Variant	Prod. no.	GBP
● black 600 lm | 3000 K	**1007979**	**59.00**
● black 400 lm | 2200 K	**1011598** ●	**61.00**

SYNA
SP





IP55 IK04 50° 180° 30000 h L70B50 150

220-240 V ~50/60 Hz
Total wattage: 9 W
Material: Aluminium

- IP44 safety plug

INSIDE CRI 80


	3000 K 470 lm

Variant	Prod. no.	GBP
● anthracite	**1007977**	**69.00**

PL-BEAM PRO S
SP, DALI

NEW





Dali IP66 IK08 23/64° 50000h L80B20

220-240 V ~50/60 Hz | 600 mA
Total wattage: 12 W
Material: Aluminium/Glass

- A versatile spotlight, suitable for use as a façade or mast light.

LED INSIDE CRI 80

1012113	2700 K 1400 lm
1012114	2700 K 1300 lm
1012115	2200 K 1300 lm
1012116	2200 K 1250 lm
1012127	3000 K 1450 lm
1012128	3000 K 1400 lm

Variant	Prod. no.	GBP
● anthracite 1400 lm | 2700 K | 23°	**1012113**	**172.00**
● anthracite 1300 lm | 2700 K | 64°	**1012114**	**172.00**
● anthracite 1300 lm | 2200 K | 23°	**1012115**	**172.00**
● anthracite 1250 lm | 2200 K | 64°	**1012116**	**172.00**
● anthracite 1450 lm | 3000 K | 23°	**1012127**	**172.00**
● anthracite 1400 lm | 3000 K | 64°	**1012128**	**172.00**


⊕

Product	Prod. no.	GBP
Wall bracket		
● black	**234350**	**34.00**
Lamp shield		
● anthracite	**1012131**	**13.00**
Honeycomb grid		
● black	**1012133**	**5.00**
Mast clamp		
● anthracite	**1012135**	**17.00**

PL-BEAM PRO S
SP, DALI, ASYM

NEW





Dali IP66 IK08 33/25° 50000h L80B20

220-240 V ~50/60 Hz | 600 mA
Total wattage: 12 W
Material: Aluminium/Glass

- A versatile spotlight, suitable for use as a façade or mast light.

LED INSIDE CRI 80

1012117	2700 K 1350 lm
1012118	2200 K 1250 lm
1012125	3000 K 1450 lm

Variant	Prod. no.	GBP
● anthracite 1350 lm | 2700 K	**1012117**	**172.00**
● anthracite 1250 lm | 2200 K	**1012118**	**172.00**
● anthracite 1450 lm | 3000 K	**1012125**	**172.00**


⊕

Product	Prod. no.	GBP
Wall bracket		
● black	**234350**	**34.00**
Lamp shield		
● anthracite	**1012131**	**13.00**
Honeycomb grid		
● black	**1012133**	**5.00**
Mast clamp		
● anthracite	**1012135**	**17.00**

PL-BEAM PRO M
SP, DALI

NEW





Dali IP66 IK08 23°/64° 70000h L80B20

220-240 V ~0/50/60 Hz | 700 mA
Total wattage: 26 W
Material: Aluminium/Glass

- A versatile spotlight, suitable for use as a façade or mast light.

LED INSIDE CRI 80

1012119	2700 K 3350 lm
1012120	2700 K 3200 lm
1012121	2200 K 3050 lm
1012122	2200 K 2900 lm
1012129	3000 K 3500 lm
1012130	3000 K 3300 lm

Variant	Prod. no.	GBP
● anthracite 3350 lm | 2700 K | 23°	**1012119** ●	**285.00**
● anthracite 3200 lm | 2700 K | 64°	**1012120** ●	**285.00**
● anthracite 3050 lm | 2200 K | 23°	**1012121** ●	**285.00**
● anthracite 2900 lm | 2200 K | 64°	**1012122** ●	**285.00**
● anthracite 3500 lm | 3000 K | 23°	**1012129** ●	**285.00**
● anthracite 3300 lm | 3000 K | 64°	**1012130** ●	**285.00**


⊕

Product	Prod. no.	GBP
Wall bracket		
● black	**234350** ●	**34.00**
Lamp shield		
● anthracite	**1012132** ●	**17.00**
Honeycomb grid		
● black	**1012134** ●	**10.00**
Mast clamp		
● Anthracite	**1012135** ●	**17.00**

PL-BEAM PRO M
SP, DALI, ASYM

NEW





Dali IP66 IK08 33/25° 70000h L80B20

220-240 V ~0/50/60 Hz | 700 mA
Total wattage: 26 W
Material: Aluminium/Glass

- A versatile spotlight, suitable for use as a façade or mast light.

LED INSIDE CRI 80

1012123	2700 K 3300 lm
1012124	2200 K 3000 lm
1012126	3000 K 3400 lm

Variant	Prod. no.	GBP
● anthracite 3300 lm | 2700 K	**1012123** ●	**285.00**
● anthracite 3000 lm | 2200 K	**1012124** ●	**285.00**
● anthracite 3400 lm | 3000 K	**1012126** ●	**285.00**

⊕

Product	Prod. no.	GBP
Wall bracket		
● black	**234350** ●	**34.00**
Lamp shield		
● anthracite	**1012131** ●	**13.00**
Honeycomb grid		
● black	**1012133** ●	**5.00**
Mast clamp		
● anthracite	**1012135** ●	**17.00**





PL-BEAM PRO S
LAMP SHIELD

NEW



Ø: 9.4 cm
H: 0.4 cm
Material: Aluminium

Variant	Prod. no.	GBP
anthracite	1012131	13.00

PL-BEAM PRO S
HONEYCOMB GRID

NEW



L: 13.7 cm
B: 13.8 cm
H: 7.4 cm
Material: Aluminium

Variant	Prod. no.	GBP
black	1012133	5.00

PL-BEAM PRO S/M
MAST CLAMP

NEW



L: 15 cm
W: 3.5 cm
H: 9.2 cm
Material: Aluminium

Variant	Prod. no.	GBP
anthracite	1012135	17.00

PL-BEAM PRO M
LAMP SHIELD

NEW




Ø: 13.3 cm
H: 0.4 cm
Material: Aluminium

Variant	Prod. no.	GBP
anthracite	1012132	17.00

PL-BEAM PRO M
HONEYCOMB GRID

NEW



L: 17.7 cm
W: 17.8 cm
H: 8.4 cm
Material: Aluminium

Variant	Prod. no.	GBP
black	1012134	10.00

PL-BEAM
WALL BRACKET

NEW




L: 82 cm
W: 18 cm
H: 11 cm
Material: Steel

Variant	Prod. no.	GBP
black	234350	34.00

GALEN 60
SP







220-240 V ~50/60 Hz | 450 mA
Total wattage: 18 W
Material: Aluminium




3000 K	4000 K
1570 lm	1570 lm

Variant	Prod. no.	GBP
● anthracite	**1003447**	**201.00**

Product	Prod. no.	GBP
5m connection cable with open cable end		
● black	**231960**	**25.00**
Connecting cable 1 m		
● black	**231961**	**17.00**

GALEN 120
SP







220-240 V ~50/60 Hz | 900 mA
Total wattage: 34 W
Material: Aluminium

• IP67 plug-in system




3000 K	4000 K
3000 lm	3100 lm

Variant	Prod. no.	GBP
● anthracite	**1003448**	**294.00**

Product	Prod. no.	GBP
5m connection cable with open cable end		
● black	**231960**	**25.00**
Connecting cable 1 m		
● black	**231961**	**17.00**

GALEN PRO 60
WL, DALI





Dali Touch IP65 IK06 26/54° 180° 50 000 h L80B20 17

220-240 V ~0/50/60 Hz | 305 mA
Total wattage: 20 W
Material: Aluminium/Glass

- Asym. light distribution for optimum illumination of paths
- IP connection box

LED INSIDE CRI 80

3000 K
2300 lm


Variant	Prod. no.	GBP
● anthracite	**1009107**	**373.00**

⊕

Product	Prod. no.	GBP
wall mount extension		
● black	**234350**	**34.00**

GALEN PRO 120
WL, DALI





Dali Touch IP65 IK06 26/54° 180° 50 000 h L80B20 17

220-240 V ~0/50/60 Hz | 335 mA
Total wattage: 40 W
Material: Aluminium/Glass

- Asym. light distribution for optimum illumination of paths
- IP connection box

LED INSIDE CRI 80

3000 K
5150 lm


Variant	Prod. no.	GBP
● anthracite	**1009108**	**462.00**

⊕

Product	Prod. no.	GBP
wall mount extension		
● black	**234350**	**34.00**

HELIA SPOT S
SP, SINGLE





IP66 IK04 35° 330° 90° 30000h L70B50 300

220-240 V ~50/60 Hz | 500 mA
Total wattage: 6.5 W
Material: Aluminium

- IP44 safety plug

LED INSIDE CRI 80

3000 K
440 lm


Variant	Prod. no.	GBP
anthracite	**1007944**	**151.00**

⊕

Product	Prod. no.	GBP
Ground spike		
stainless steel	**1000736**	**20.00**

HELIA SPOT L
SP, SINGLE, PHASE





C IP66 IK04 40° 320° 90° 40000h L70B50 300

220-240 V ~50/60 Hz | 700 mA
Total wattage: 15 W
Material: Aluminium

- IP44 safety plug

LED INSIDE CRI 80

3000 K
1340 lm


Variant	Prod. no.	GBP
anthracite	**1007943**	**197.00**

⊕

Product	Prod. no.	GBP
Ground spike		
stainless steel	**228560**	**24.00**

FLAC BEAM
SP





IP65 IK04 60° 120° 170° 50000 h L70B50 200

220-240 V ~50/60 Hz
Total wattage: 27 W
Material: Aluminium

- IP44 safety plug


LED INSIDE CRI 80

3000 K
1600 lm

Variant	Prod. no.	GBP
grey	**1007942**	**419.00**

SAMRINA
SP, SINGLE, GU10





IP65 IK04 280° 150

220-240 V ~50/60 Hz
Material: Plastic

- Contains recycled material
- IP44 safety plug

SOCKET INSIDE 7 W

Base: GU10 | max. Ø: 6 cm | L: 6 cm

Variant	Prod. no.	GBP
black	**1007972**	**40.00**

GU10 | 6 W | 38°
450 lm | 2700 K | EEC = F

C,L


Prod. no.: **1005077** **7.00 GBP**



231035 742

NAUTILUS 10
SP, SQUARE







100-277 V ~50/60 Hz | 700 mA
Total wattage: 8.5 W
Material: Aluminium/Glass

- IP44 safety plug




3000 K
660 lm

Variant	Prod. no.	GBP
● anthracite	**1007958**	**126.00**

NAUTILUS 10
SP, ROUND, QPAR51





IP65 IK04 180° 150

220-240 V ~50/60 Hz
Material: Aluminium

- IP44 safety plug

SOCKET INSIDE 10 W

Base: 1xGU10 | L: 5.7 cm

Variant	Prod. no.	GBP
grey	**1007956**	**26.00**


GU10 | 6 W | 38°
450 lm | 2700 K | EEC = F

Prod. no.: 1005077 7.00 GBP

Better value as a set at ks-light.co.uk

BIG NAUTILUS
SP, ROUND, QPAR51





IP44/IP65 IK06 180° 150

220-240 V ~50/60 Hz
Material: Aluminium

- Ground spike made from recycled plastic
- IP44 safety plug

SOCKET INSIDE 11 W

Base: 1xGU10 | max. Ø: 5.1 cm | L: 8.3 cm

Variant	Prod. no.	GBP
black	**1007955**	**26.00**
rust	**1008030**	**26.00**
green	**1007960**	**26.00**

GU10 | 6 W | 38°
450 lm | 2700 K | EEC = F

Prod. no.: 1005077 7.00 GBP


SMART

GU10 | 5 W | 100°
300 lm | 2000 K-6500 K | EEC = G

Prod. no.: 1012470 29.00 GBP

NAUTILUS 10
SP, ROUND, QPAR51





IP55 IK04 180° 150

220-240 V ~50/60 Hz
Material: Stainless steel 316

- IP44 safety plug

SOCKET INSIDE 25 W

Base: 1xGU10 | max. Ø: 5.1 cm | L: 5.7 cm

Variant	Prod. no.	GBP
stainless steel	**1007957**	**88.00**

GU10 | 6 W | 38°
450 lm | 2700 K | EEC = F

Prod. no.: 1005077 7.00 GBP


SMART

GU10 | 5 W | 100°
300 lm | 2000 K-6500 K | EEC = G

Prod. no.: 1012470 29.00 GBP

NAUTILUS
SP, QR-C51





IP67 IK03 180° 150

12 V 50/60 Hz
Material: Stainless steel 304/glass

- Open cable end

SOCKET INSIDE 35 W

Base: 1xGX5.3


Variant	Prod. no.	GBP
stainless steel	229090	77.00

GU5.3 | 6 W | 36°
450 lm | 2700 K | EEC = G

Prod. no.: 1001574 30.00 GBP

NAUTILUS 10 SPOT
SP, QPAR51





IP55 IK03 360° 180° 150

220-240 V ~50/60 Hz
Material: Stainless steel 316

- Open cable end

SOCKET INSIDE 25 W

Base: 1xGU10 max. Ø: 5.1 cm | L: 6 cm

Variant	Prod. no.	GBP
stainless steel	229741	88.00

GU10 | 6 W | 38°
450 lm | 2700 K | EEC = F

Prod. no.: 1005077 7.00 GBP

SMART


GU10 | 5 W | 100°
300 lm | 2000 K-6500 K | EEC = G

Prod. no.: 1012470 29.00 GBP

Product	Prod. no.	GBP
Connection box IP68, 3-pin		
black	228730	16.00

NAUTILUS 10 SPOT
SP, LED





IP55 IK04 60° 180° 30000 h L70B50

220-240 V ~50/60 Hz
Total wattage: 9 W
Material: Stainless steel 316

- IP44 safety plug

LED INSIDE CRI 80


3000 K
690 lm

Variant	Prod. no.	GBP
stainless steel	1007959	100.00

Product	Prod. no.	GBP
Plastic ground spike		
black	900011	4.00
Mounting plate		
stainless steel	1001963	8.00

DASAR® PROJECTOR
SP, 12/24V





IP68 IK04 40° 90° 25000h L70B50 250

12-24 V
Power consumption: 6.5 W
Material: Stainless steel 316/glass

- Open cable end

LED INSIDE CRI 80

3000 K
520 lm


Variant	Prod. no.	GBP
stainless steel	**233570**	**208.00**

⊕

Product	Prod. no.	GBP
Stainless steel 316 ground spike		
stainless steel	**233580**	**17.00**
Stainless steel 316 mounting plate		
stainless steel	**233582**	**23.00**
Plastic ground spike		
black	**900011**	**4.00**
LED power supply 12V | 24W, round		
white	**1008651**	**23.00**
LED power supply 24V | 25W, round		
white	**1008652**	**23.00**

DASAR® 920
SP, 230V





IP67 IK04 40° 90° 25000h L70B50 200

220-240 V ~50/60 Hz | 400 mA
Total wattage: 4.6 W
Material: Stainless steel 316/glass

- IP44 safety plug

LED INSIDE CRI 80

3000 K
300 lm

Variant	Prod. no.	GBP
stainless steel	**1007934**	**260.00**

⊕

Product	Prod. no.	GBP
Stainless steel 316 ground spike		
stainless steel	**233580**	**17.00**
Stainless steel 316 mounting plate		
stainless steel	**233582**	**23.00**
Plastic ground spike		
black	**900011**	**4.00**


1007868 747

HELIA SLIM
POLE, SINGLE



IP65 IK03 38° 180° 50000h L70B50 150

220-240 V ~50/60 Hz | 150 mA
Total wattage: 6 W
Material: Aluminium

- IP44 safety plug

LED INSIDE CRI 80

1007868 Spot	3000 K	450 lm
1011034 Spot	2200 K	500 lm

Variant	Prod. no.	GBP
● black 450 lm | 3000 K	**1007868**	**121.00**
● black 500 lm | 2200 K	**1011034** ●	**117.00**

HELIA SLIM
POLE, DOUBLE



IP65 IK03 38° 180° 50000h L70B50 150

220-240 V ~50/60 Hz | 150 mA
Total wattage: 12 W
Material: Aluminium

- IP44 safety plug

LED INSIDE CRI 80


1007869 Spot 1	3000 K	450 lm
1007869 Spot 2	3000 K	450 lm
1011033 Spot 1	2200 K	500 lm
1011033 Spot 2	2200 K	500 lm

Variant	Prod. no.	GBP
● black 450 lm | 3000 K	**1007869**	**147.00**
● black 500 lm | 2200 K	**1011033** ●	**142.00**


1004652 749

THEO BRACKET
SP





IP44/ IP65 | IK02 | 70° | 150

220-240 V ~50/60 Hz
Material: Aluminium/Glass

- IP44 safety plug

SOCKET INSIDE 7 W

Base: 1xGU10 | max. Ø: 5.1 cm | L: 5.7 cm

Variant	Prod. no.	GBP
anthracite	**1007981**	**56.00**


GU10 | 6 W | 38°
450 lm | 2700 K | EEC = F

C,L

Prod. no.: 1005077 7.00 GBP

LED SPIKE
SP





IP55 | IK06 | 40° | 30000 h L80B50 | 150

100-240 V ~50/60 Hz | 240 mA
Total wattage: 6 W
Material: Aluminium/Glass

- IP44 safety plug

LED INSIDE CRI 80

3000 K
400 lm


Variant	Prod. no.	GBP
anthracite	**1007949**	**61.00**
rust	**1007950**	**61.00**



231535 751

SITRA 360 SPIKE
SP, SINGLE, TCR-TSE





IP44 IK04 90° 150

220-240 V ~50/60 Hz
Material: Aluminium/Glass

- Ground spike made from recycled plastic
- IP44 safety plug

SOCKET INSIDE 9 W

Base: 1xG53 | max. Ø: 7.5 cm | L: 3.5 cm

Variant	Prod. no.	GBP
● anthracite	**1007973**	**55.00**


GX53 | 6 W | 120°
490 lm | 2700 K | EEC = G

C,L

Prod. no.: 1005272 10.00 GBP

SITRA 360 SPIKE
SP, DOUBLE, TCR-TSE





IP44 IK04 90° 90° 150

220-240 V ~50/60 Hz
Material: Aluminium/Glass

- IP44 safety plug

SOCKET INSIDE 9 W

Base: 2xG53 | max. Ø: 7.5 cm | L: 3.5 cm

Variant	Prod. no.	GBP
● anthracite	**1007974**	**164.00**

GX53 | 6 W | 120°
490 lm | 3000 K | EEC = G

C,L

Prod. no.: 1005271 10.00 GBP

SYMBOLS KEY

Recommendations
Displays accessories and recommended light bulbs for the chosen products

Mix & Match
Indicates products that can be combined

Energy efficiency class
"This light is suitable for bulbs with an energy efficiency rating of ..."

Protection classes
- Protection class I / Protective conductor
- Protection class II/ Protection by double or reinforced insulation
- Protection class III/ Protection by extra-low voltage

Dimmable with:
- **C** = Trailing-edge phase dimmer
- **L** = Leading-edge phase dimmer
- **Uni** = Universal dimmer
- **1–10 V**
- **Dali** = DALI bus system
- **Switch** = Switch/button or touch control on the light
- **Touch** = Simple, stepless operation; responds to touch

IP protection rating:
Indicates the suitability of electrical equipment for different environmental conditions.

IK impact resistance rating:
The IK impact resistance rating is a measure of the resistance of housings for electrical equipment to mechanical stress, especially impact stress.

Half-diffusion angle:
Describes the beam angle in degrees. The smaller the angle, the more concentrated the light will be.

Rotation and pivoting capacity in degrees:
- Rotation range
- Pivot range
- Gimballed

Preservation of luminous flux:
Describes the amount by which the luminous flux of an LED decreases during a specified period.

Unified Glare Rating:
The lower the UGR value, the lower the psychological glare.

Pendant cable length
in cm

Cable length:
Mains plugs, connectors and supply cables (with open cable end) in cm

Through-wiring possible

Shape of the installation opening

Specification of the installation depth

Drive-over capability of the product ensured

Weight-bearing capacity of the product up to the specified value in tonnes. Measurements based on installation in concrete.

Sea-air resistant coating

Independent converter:
Control equipment also for use outside of lights

Short-circuit protected safety control equipment

Light colour temperature in Kelvin (K)

Luminous flux in lumens (lm)

Dark Sky
Indicates that the light emits almost no light into the upper half-space (ULOR < 2 %). Reduces light pollution and ensures targeted, needs-based illumination of the usable area.

Primary/Replica
Indicates lights with integrated primary/replica function. A sensor light (primary) controls downstream lights (replica) via a switched phase, enabling simple, networked lighting control without additional bus or control systems.

Connected lighting:
Indicates smart products that use the following protocols:
- Zigbee®
- DALI
- Bluetooth

Allows the installation of electrical control equipment on materials whose flammability is not known.

CCT switch:
By means of an integrated CCT switch, the light colour can be changed from 2700 K, 3000 K, 4000 K to 6500 K during installation.

Dim-to-warm:
With dimmers, the light colour can be altered from cold white to warm white.

Indicates lights with RGB+W and RGB
(Red-Green-Blue + White and Red-Green-Blue)

Indicates lights with motion sensors
(Microwaves (MR) - Technology / Infrared / Radio)

Products with integrated LEDs

Products with light socket

KS Licht – Your lighting wholesaler in Essen

Contact, customer service and information for customers
BIG WHITE 2027

Directly linked to our product range, advice and project services:

In the KS Multi Brand Business online shop, you will find the latest products, new releases and special offers, as well as information to support you with advice, quotations and project management:

- Online stock availability check
- Catalogues, browsable catalogues and product links
- Technical data, tender specifications, light distribution curves and LDT files
- Easily find and order spare parts
- View your individual terms and conditions, delivery and payment terms
- Relevant product recommendations, variants and alternative products
- Direct contact with our sales team

Customer Information

All prices are net, plus statutory VAT. The retail prices quoted are recommended retail prices. Upon publication of this catalogue, previous price lists cease to be valid.
Illustrations, colours, shapes, designs and technical specifications are for illustrative purposes only and are not binding. Subject to changes and errors.
Goods are generally dispatched ex works, carriage forward.
For orders with a net value of less than €70.00, a minimum order surcharge of €8.00 will be applied.

Ordering & Delivery

When placing orders, please always specify the item number, colour and quantity. This reduces the need for follow-up enquiries and speeds up processing.
Express and direct deliveries are available on request.
Custom-made items, components assembled to the customer's specifications and lamps are excluded from exchange.
Our General Terms and Conditions apply and are available at www.ks-germany.com/de/agb.

Kontakt

KS Licht- und Elektrotechnik GmbH
Manderscheidtstraße 8 c
45141 Essen
Germany

Verkauf & Service
Tel.: +49 (0)201-89924-0
verkauf@ks-germany.com

Online
ks-light.co.uk
www.ks-germany.com

Pflichtangaben

KS Licht- und Elektrotechnik GmbH · Sitz der Gesellschaft: Essen · Geschäftsführer: Kai Becker
Registergericht: Amtsgericht Essen · Handelsregister: HRB 12736 · Steuer-Nr.: 111/5708/2689 ·
USt-IdNr.: DE190673411

KS Licht- und Elektrotechnik GmbH
Manderscheidtstraße 8 c
45141 Essen
Germany

Tel.: +49 (0)201-89924-0

B2B-Shop: **ks-light.co.uk**
Website: www.ks-germany.com
E-Mail: verkauf@ks-germany.com

Opening hours
Monday – Thursday 08:00 – 16:30
Friday 08:00 – 15:00