

Art.-Nr.: 798.80
798.81
798.82
798.83

798.80_798.81

798.82
798.83

Li-Ion

PPN 07/22

CE UK CA

A

798.80 Driver: 24VA
798.81 Driver: 36VA

798.80: 1,5m
798.81: 3m
798.82: 1m
798.83: 2,5m

167mm

off

B

Installation diagrams showing correct and incorrect mounting methods.

Correct: $r > 30\text{mm}$, $a \geq 60^\circ$

Incorrect: $r < 30\text{mm}$, $a < 60^\circ$

Checkmarks and X marks indicating correct and incorrect practices.

C

5m 120° 5m < 7m

Li-Ion

only use CR2025
1x Li-Ion Battery (3V 150mAH)

D

expandable

Driver 24VA → max.3m
Driver 36VA → max.5m

IP20 IP44

Water Protection
Art.-Nr.: 702.47

E

RGBW Controller

R.G.B.W

on

F

G

RGBW Controller

H

25%
50%
75%
100%

I

RGBW Controller

FLASH

J

RGBW Controller

AUTO

K

RGBW Controller

QUICK
SLOW

L

RGBW Controller

JUMP3

M

RGBW Controller

JUMP7

N

RGBW Controller

FADE7

O

RGBW Controller

FADE7

